



Non-Pressure fittings



Field of application:
Plastics piping systems for soil and waste discharge (low & high temperature) inside buildings -(PVC-U)

Material: UPVC
Colour: Light Grey
Dimension: mm
Tradename: PPP

GENERAL TECHNICAL SPECIFICATION

General Characteristics

- Fitting Appearance

Physical Characteristics

- Vicat Softening Temperature
- Effects of heating
- Markings

Standard Requirements

Without magnification, the internal/external surface shall be smooth, clean & free from grooving, blistering, impurities, pores or any other surface irregularity likely to prevent conformity to this international standard

≥79°C @ 50N load (As per Clause 8.2)
As per Clause 8.2 (EN 763)
Temp 150° C ± 2°C
As per Clause 12.3

Light Grey		White	
Description	Size	Description	Size
Tee/Elbow	40/50/75/100/110mm	Pan Adaptor	125/110mm
Y 45°	75 & 110mm	Male Adaptor	20/25mm
Elbow 45°	50, 75 & 110mm	Female Adaptor	20/25mm
Male End Cap	40/50, 75/110mm	Male/Female Adaptor	32mm
Female End Cap	40/50, 75/110mm	Tee	20/25mm
UL Reducer	40/50mm	Elbow	20/25mm
UL Nuts	40/50mm	TEE/Elbow	32mm

Imported range : 63/90/160/200/250 mm

Manufactured by PPP Piping Systems Ltd - Certified MS ISO 9001:2008 & MS ISO 14001:2004
MSB Test Report available on request (conditions apply)

Email: info@str.mu | website: www.str.mu